

MATERIAL: NYLON 66(UL) FLAME CLASS: 94V-0,94V-2 COLOR: BLACK, NATURAL UNIT: mm


用途: 机板部份用M3铁板自攻螺丝固定,另一头直


用途:

用途:

接压入PC板。








PART NO	PACKAGE
PCSS-037	1000


PC板与PC板间之固定,不占空间




MATERIAL: NYLON 66(UL) FLAME CLASS: 94V-0,94V-2 COLOR: BLACK, NATURAL


UNIT: mm








PART NO	PACKAGE
PCSS-038	1000



MATERIAL: NYLON 66(UL) FLAME CLASS: 94V-0,94V-2 COLOR: BLACK, NATURAL


UNIT: mm



机板部分用M3.5铁板自攻螺丝固定,	另
一头直接压入PC板。	




PART NO	PACKAGE
PCSS-039	1000



MATERIAL: NYLON 66(UL) FLAME CLASS: 94V-0,94V-2 COLOR: BLACK, NATURAL

UNIT: mm



PART NO	Α	PACKAGE
PCSS-040	5.6	1000
PCSS-041	8.0	1000
PCSS-042	11.9	1000

背胶式,用于不能钻孔之机板与PC板间 用途: 之固定

高度不含背胶及离型纸厚度